# MELT PENDANT MINI LED



Melt is evocative of molten glass, the interior of a melting glacier or images of deep space. An imperfect, organic and naturalistic light that produces a mesmerizing hot-blown glass effect. Melt is created through a process of blow moulding and vacuum metallisation to achieve melted orbs with abundant and unusual luminosity that reflects and enhances its environment.

2014 Year of Design 2.40 lb **Product Weight** 

**Finishing Process** Semi-Metallised, Plated

Surface Mount Shape/Diameter Dome, 4.5 in **Power Method** Mains

SPT-2, 2x18AWG, 300 V Cable Spec

Cable Type/Length Clear, 98.4 in 6W LED **Light Source** Max Wattage 9W 800 Lumens CRI >90 **Colour Temperature** 3000K

Dimmability Mains Dimmable, Leading & Trailing Edge

Voltage 100-120V **Environment** Indoor

LEDRING01Y, LEDDRIVER01UL Spares

Certification

### COPPER

Code MES04CO-PUSM2 **Shade Code** MES02CO **Shade Material Polycarbonate** Shade Colour/Finish Copper, Mirrored LEDP07COUL Fitting Code Fitting Material

Fitting Colour/Finish Copper, Polished

Service Offer Quick Ship

## **SMOKE**

Code MES04SM-PUSM2 **Shade Code** MES02SM **Shade Material Polycarbonate** Shade Colour/Finish Smoke, Mirrored Fitting Code LEDP07CHUL

Fitting Material Steel

Fitting Colour/Finish Silver, Polished Service Offer Quick Ship





# MELT PENDANT MINI LED



Melt is evocative of molten glass, the interior of a melting glacier or images of deep space. An imperfect, organic and naturalistic light that produces a mesmerizing hot-blown glass effect. Melt is created through a process of blow moulding and vacuum metallisation to achieve melted orbs with abundant and unusual luminosity that reflects and enhances its environment.

Year of Design 2014 Product Weight 2.40 lb

Finishing Process Semi-Metallised, Plated

Surface Mount Shape/Diameter Dome, 4.5 in Power Method Mains

Cable Spec SPT-2, 2x18AWG, 300 V

Cable Type/LengthClear, 98.4 inLight Source6W LEDMax Wattage9WLumens800CRI>90Colour Temperature3000K

**Dimmability** Mains Dimmable, Leading & Trailing Edge

Voltage 100-120V Environment Indoor

Spares LEDRING01Y, LEDDRIVER01UL

Certification T24

### **SILVER**

Code MES04CH-PUSM2
Shade Code MES02CH
Shade Material Polycarbonate
Shade Colour/Finish Silver, Mirrored
Fitting Code LEDP07CHUL
Fitting Material Steel
Fitting Colour/Finish Silver, Polished

Service Offer Quick Ship

## GOLD

Code MES04GO-PUSM2
Shade Code MES02G
Shade Material Polycarbonate
Shade Colour/Finish Gold, Mirrored
Fitting Code LEDP07GOUL
Fitting Material Steel

Fitting Colour/Finish Gold, Polished
Service Offer Quick Ship

