


# MELT CHANDELIER SMALL LED



Melt is evocative of molten glass, the interior of a melting glacier or images of deep space. An imperfect, organic and naturalistic light that produces a mesmerizing hot-blown glass effect. Melt is created through a process of blow moulding and vacuum metallisation to achieve melted orbs with abundant and unusual luminosity. Melt Chandelier Small features four orbs protruding from steel tubes.

Year of Design	2020
Product Weight	20.40 lb
Finishing Process	Semi Metallised, Plated
Surface Mount Shape/Diameter	Dome, 10 in
Power Method	Mains
Cable Spec	SPT-2, 2x18AWG, 300 V
Cable Type/Length	Clear, 196.9 in
Light Source	4 x 6W LED
Max Wattage	30W
Lumens	2300
CRI	>90
Colour Temperature	3000K
Dimmability	Mains Dimmable, Leading & Trailing Edge
Voltage	100-120V
Environment	Indoor
Spares	LEDRING02A, LEDCDRIVER01UL
Certification	T24



COPPER	
Code	MEC01CO-CUSM4
Shade Code	4 X MES01CO
Shade Material	Polycarbonate
Shade Colour/Finish	Copper, Mirrored
Fitting Code	LEDC01GOUL
Fitting Material	Steel
Fitting Colour/Finish	Gold, Polished
Service Offer	Collection


SMOKE	
Code	MEC01SM-CUSM4
Shade Code	4 X MES01SM
Shade Material	Polycarbonate
Shade Colour/Finish	Smoke, Mirrored
Fitting Code	LEDC01CHUL
Fitting Material	Steel
Fitting Colour/Finish	Silver, Polished
Service Offer	Collection

# MELT CHANDELIER SMALL LED



Melt is evocative of molten glass, the interior of a melting glacier or images of deep space. An imperfect, organic and naturalistic light that produces a mesmerizing hot-blown glass effect. Melt is created through a process of blow moulding and vacuum metallisation to achieve melted orbs with abundant and unusual luminosity. Melt Chandelier Small features four orbs protruding from steel tubes.

Year of Design	2020
Product Weight	20.40 lb
Finishing Process	Semi Metallised, Plated
Surface Mount Shape/Diameter	Dome, 10 in
Power Method	Mains
Cable Spec	SPT-2, 2x18AWG, 300 V
Cable Type/Length	Clear, 196.9 in
Light Source	4 x 6W LED
Max Wattage	30W
Lumens	2300
CRI	>90
Colour Temperature	3000K
Dimmability	Mains Dimmable, Leading & Trailing Edge
Voltage	100-120V
Environment	Indoor
Spares	LEDRING02A, LEDCDRIVER01UL
Certification	T24



## SILVER

Code	MEC01CH-CUSM4
Shade Code	4 X MES01CH
Shade Material	Polycarbonate
Shade Colour/Finish	Silver, Mirrored
Fitting Code	LEDC01CHUL
Fitting Material	Steel
Fitting Colour/Finish	Silver, Polished
Service Offer	Collection

## GOLD

Code	MEC01GO-CUSM4
Shade Code	4 X MES01G
Shade Material	Polycarbonate
Shade Colour/Finish	Gold, Mirrored
Fitting Code	LEDC01GOUL
Fitting Material	Steel
Fitting Colour/Finish	Gold, Polished
Service Offer	Collection